



Obalski property: 2020-22 drilling results

| Hole | Zone | Section | Length (m)* | Au (g/t) | Ag (g/t) | Cu (%) | Depth (m) |
|---|-------------|-----------------|--------------|---------------|---------------|-------------|------------|
| OBS-20-001 | C | 450+00 E | 0.65 | 12.45 | 17.70 | 0.53 | 93 |
| | A-Po | | 0.55 | 1.93 | 1.80 | - | 234 |
| OBS-20-002 | C | 450+00 E | 1.10 | 1.38 | 1.39 | - | 100 |
| | A | | 0.50 | 67.10 | 40.10 | 2.32 | 205 |
| | D | | 0.90 | 2.59 | 3.10 | - | 236 |
| | A-Po | | 1.10 | 47.40 | 87.60 | 7.06 | 298 |
| OBS-20-003 <i>Including</i> <i>Including</i> | A-Po | 450+00 E | 11.95 | 0.51 | 1.84 | 0.12 | 276 |
| | | | 1.30 | 1.58 | 4.80 | 0.19 | |
| | | | 1.10 | 1.20 | 4.20 | 0.53 | |
| | A-Po | | 0.50 | 6.35 | 1.90 | - | 376 |
| | A-Po | | 7.10 | 0.26 | 2.13 | - | 419 |
| OBS-20-004 | A-Po | - | - | - | - | - | |
| OBS-21-005 | A-Po | 120+00 E | 4.05 | 3.01 | 3.35 | - | 200 |
| OBS-21-005A | A-Po | 120+00 E | 49.25 | 0.21 | 0.19 | 0.04 | 374 |
| OBS-21-006 | A-Po | 120+00 E | 1.90 | 0.24 | 0.68 | - | 250 |
| OBS-21-007 | A-Po | 120+00 E | 20.75 | 0.43 | 0.29 | - | 385 |
| OBS-21-008 <i>Including</i> | A-Po | 150+00 E | 12.55 | 0.85 | 1.40 | 0.11 | 185 |
| | A-Po | | 2.10 | 3.40 | 4.73 | 0.65 | |
| OBS-21-009 <i>Including</i> <i>Including</i> | A-Po | 150+00 E | 28.50 | 1.41 | 0.81 | - | 200 |
| | A-Po | | 1.50 | 6.84 | 1.50 | - | |
| | A-Po | | 4.50 | 4.03 | 2.87 | - | |
| OBS-21-010 | A-Po | 150+00 E | 45.95 | 0.32 | 0.35 | - | 425 |
| OBS-21-010A <i>Including</i> | A-Po | 150+00 E | 54.80 | 0.33 | 0.20 | - | 425 |
| | A-Po | | 3.50 | 1.44 | 0.80 | - | |
| OBS-21-011 | A-Po | 200+00 E | 0.50 | 1.60 | 2.60 | - | 210 |
| OBS-21-012 | A-Po | 200+00 E | 27.50 | 0.39 | 0.83 | - | 300 |
| OBS-21-013 | A-Po | 200+00 E | 1.40 | 0.76 | 2.10 | 0.14 | 450 |
| OBS-21-014 | A-Po | 250+00 E | 8.90 | 0.62 | 0.12 | - | 210 |
| OBS-21-014A | A-Po | 250+00 E | 7.70 | 0.89 | 0.32 | - | 230 |
| OBS-21-015 <i>Including</i> | A-Po | 250+00 E | 3.20 | 23.78 | 16.55 | 1.00 | 330 |
| | A-Po | | 0.45 | 167.50 | 112.00 | 6.08 | |
| OBS-21-015A <i>Including</i> | A-Po | 250+00 E | 10.50 | 5.06 | 3.27 | - | 360 |
| | A-Po | | 0.65 | 71.00 | 31.40 | - | |
| OBS-22-016 | A-Po | 300+00 E | 25.15 | 0.31 | 0.58 | 0.06 | 200 |
| OBS-22-017 <i>Including</i> | C | 300+00 E | 0.80 | 3.83 | 8.30 | 0.42 | 165 |
| | A-Po | | 16.95 | 0.33 | 0.09 | 0.03 | 260 |
| | A-Po | | 9.35 | 6.07 | 3.29 | 0.08 | 295 |
| | | | 0.90 | 60.60 | 31.80 | 0.60 | |
| OBS-22-018 | C | 300+00 E | 3.60 | 0.43 | 0.63 | 0.02 | 285 |
| OBS-22-019 <i>Including</i> | A-Po | 175+00 E | 52.30 | 1.83 | 0.73 | 0.04 | 350 |
| | | | 0.50 | 125.00 | 45.80 | 3.30 | |

* True width is estimated at 65-70% of core length.

Sample preparation and analysis

TomaGold has implemented and is adhering to a strict Quality Assurance/Quality Control program for the current drilling program. The core is sawed in half, with one half kept as a witness sample in Chibougamau and the other half shipped directly by bus to ALS Chemex in Val-d'Or, Quebec. ALS grinds the half core to 1/8", split it into two halves and keeps one half as a witness (reject) in Val-d'Or. ALS pulverizes the other half to minus 150 mesh, takes a 50 g sample for analysis and keeps the rest, identified as "pulp".

The technical content of this table has been reviewed and approved by André Jean, P.Eng., TomaGold's Director of Exploration and a qualified person under National Instrument 43-101.